	;	Hull
		H
•	:	×
•	:	Hall din
	;	===
	:	æ
		::::
:	:	::::
		ij
	:	F
	:	
	;	: =
=	:	
	:	ž
	:	:55
	:	1
	:	ú
	:	Has Min
	:	œ.
Ę	:	3

City

Country

Signature

Name (Print/Type)

Please type a plus sign (+) inside this box + + Under the Paperwork Reduction Act of 1995, no persons are required to respon	PTO/SB/05 (08-00) Approved for use through 10/31/2002. OMB 0651-0032 U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE and to a collection of information unless it displays a valid OMB control number.		
UTILITY PATENT APPLICATION	Attorney Docket No. KWI-003	704556	
TRANSMITTAL	First Inventor KWITEK, Benjamin J. Title Viscoelastic Grip for a Writing	」ທ ~~_≡	
(Only for new nonprovisional applications under 37 CFR 1.53(b))	Express Mail Label No.	25°5	
APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents.	ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231	78 ≣	
1. X Fee Transmittal Form (e.g., PTO/SB/17) (Submit an original and a duplicate for fee processing) Applicant claims small entity status. See 37 CFR 1.27. Specification [Total Pages 25] (preferred arrangement set forth below) - Descriptive title of the invention - Cross Reference to Related Applications - Statement Regarding Fed sponsored R & D - Reference to sequence listing, a table, or a computer program listing appendix - Background of the Invention - Brief Summary of the Invention - Brief Description of the Drawings (if filed)	7. □ CD-ROM or CD-R in duplicate, large table or Computer Program (Appendix) 8. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) a. □ Computer Readable Form (CRF) b. Specification Sequence Listing on: i. □ CD-ROM or CD-R (2 copies); or ii. □ paper c. □ Statements verifying identity of above copies ACCOMPANYING APPLICATION PARTS		
- Detailed Description - Claim(s) - Abstract of the Disclosure 4. X Drawing(s) (35 U.S.C. 113) [Total Sheets 9] 5. Oath or Declaration [Total Pages 5] a. X Newly executed (original or copy) Copy from a prior application (37 CFR 1.63 (d)) (for continuation/divisional with Box 17 completed) i. DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s)	9. Assignment Papers (cover sheet & document(s)) 10. 37 CFR 3.73(b) Statement Power of Attorney 11. English Translation Document (if applicable) 12. Information Disclosure Statement (IDS)/PTO-1449 Citations 13. Preliminary Amendment 14. X Return Receipt Postcard (MPEP 503) (Should be specifically itemized) 15. Certified Copy of Priority Document(s) (if foreign priority is claimed)	82 J	
named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b). 6. Application Data Sheet. See 37 CFR 1.76			
17. If a CONTINUING APPLICATION, check appropriate box, and supple or in an Application Data Sheet under 37 CFR 1.76: Continuation Divisional Wigner Continuation: Examiner For CONTINUATION OR DIVISIONAL APPS only: The entire disclosure of the Box 5b, is considered a part of the disclosure of the accompanying continua The incorporation can only be relied upon when a portion has been inadverted.	of prior application No.: 60 163,259 Group I Art Unit: prior application, from which an oath or declaration is supplied under tion or divisional application and is hereby incorporated by reference.	receive the followin	
18. CORRESPONDE		N §	
Customer Number or Bar Code Label (Insert Customer No. or Attach bar Code)	or Correspondence address below	401 a	
Name		27 TO	
Address			

Burden Hour Statement: This form is estimated to take 0.2 hours to complete Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO. Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Howard N. Flaxman

State

Telephone

Zip Code

Fax

Date

34,595

11/3/2000

Registration No. (Attorney/Agent)

11/3/2000

PTO/SB/17 (09-00)

Approved for use through 10/31/2002. OMB 0651-0032

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

FEE TRANSMITTAL for FY 2001

Patent fees are subject to annual revision.

TOTAL AMOUNT OF PAYMENT

i,n

ļ. <u>.</u>

Signature

(4) 355.00	(\$)	355.	00
------------	------	------	----

Complete if Known			
Application Number			
Filing Date			
First Named Inventor	KWITEK, Benjamin J.		
Examiner Name			
Group Art Unit			
Attorney Docket No.	kWI-003		

METHOD OF PAYMENT	FEE CALCULATION (continued)				
1. The Commissioner is hereby authorized to charge indicated fees and credit any overnayments to	3. ADDITIONAL FEES				
indicated fees and credit any overpayments to. Deposit	Large Entity Small Entity				
Account 01–2221	Fee Fee Fee Fee Code (\$) Fee Description Fee	ee Paid			
Number Deposit	105 130 205 65 Surcharge - late filing fee or oath				
Account Name Aquilino & Welsh	127 50 227 25 Surcharge - late provisional filing fee or cover sheet				
Charge Any Additional Fee Required Under 37 CFR 1.16 and 1.17	139 130 139 130 Non-English specification				
Applicant claims small entity status.	147 2,520 147 2,520 For filing a request for ex parte reexamination				
See 37 CFR 1.27	112 920* 112 920* Requesting publication of SIR prior to				
2. X Payment Enclosed: X Check Credit card Money Order Other	Examiner action 113 1,840* 113 1,840* Requesting publication of SIR after Examiner action				
FEE CALCULATION	115 110 215 55 Extension for reply within first month				
1. BASIC FILING FEE	116 390 216 195 Extension for reply within second month				
Large Entity Small Entity	117 890 217 445 Extension for reply within third month				
Fee Fee Fee Fee Description	118 1,390 218 695 Extension for reply within fourth month				
Code (\$) Code (\$) Fee Paid	128 1,890 228 945 Extension for reply within fifth month				
101 710 201 355 Utility filing fee 106 320 206 160 Design filing fee	119 310 219 155 Notice of Appeal				
	120 310 220 155 Filing a brief in support of an appeal				
107 490 207 245 Plant filing fee 108 710 208 355 Reissue filing fee	121 270 221 135 Request for oral hearing				
	138 1,510 138 1,510 Petition to institute a public use proceeding				
	140 110 240 55 Petition to revive - unavoidable				
SUBTOTAL (1) (\$) 355	141 1,240 241 620 Petition to revive - unintentional				
2. EXTRA CLAIM FEES	142 1,240 242 620 Utility issue fee (or reissue)				
Fee from Ext <u>ra Clai</u> ms <u>below</u> Fee Paid	143 440 243 220 Design issue fee				
Total Claims 20 -20** = X = =	144 600 244 300 Plant issue fee				
Independent 2 - 3** = X = =	122 130 122 130 Petitions to the Commissioner				
Multiple Dependent	123 50 123 50 Petitions related to provisional applications				
	126 240 126 240 Submission of Information Disclosure Stmt				
Large Entity Small Entity					
Fee Fee Fee Fee Description Code (\$) Code (\$)	581 40 581 40 Recording each patent assignment per property (times number of properties)				
103 18 203 9 Claims in excess of 20	146 710 246 355 Filing a submission after final rejection (37 CFR § 1.129(a))				
102 80 202 40 Independent claims in excess of 3	149 710 249 355 For each additional invention to be	1			
104 270 204 135 Multiple dependent claim, if not paid	examined (37 CFR § 1.129(b))				
109 80 209 40 ** Reissue independent claims over original patent	179 710 279 355 Request for Continued Examination (RCE)				
110 18 210 9 ** Reissue claims in excess of 20 and over original patent	169 900 169 900 Request for expedited examination of a design application				
SUBTOTAL (2) (\$) 0	Other fee (specify)				
**or number previously paid, if greater; For Reissues, see above	Reduced by Basic Filing Fee Paid SUBTOTAL (3) (\$) 0				
SUBMITTED BY	Complete (families	=			
Jame (BrintlTune)	Complete (if applicable)				
Howard N. Flaxman	(Attorney/Agent) 34,595 Telephone (703) 920-	1122			

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE APPLICATION FOR LETTERS PATENT

INVENTOR: Benjamin J. Kwitek

TITLE: VISCOELASTIC GRIP FOR A WRITING IMPLEMENT

5

CROSS-REFERENCE TO RELATED APPLICATIONS

This U.S. Patent Application is based upon U.S. Provisional Patent Application Serial No. 60/163,259, filed November 3, 1999, and entitled "VISCOELASTIC GRIP FOR A WRITING IMPLEMENT". This U.S. patent application is further a Continuation-In-Part of U.S. Patent Application Serial No. 09/173,445, filed October 16, 1998, and entitled "GOLF GRIP", which is currently pending, and incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The invention relates to grips for hand held implements. More particularly, the invention relates to a writing implement grip including a responsive polymer designed to provide individuals with a soft and individually conforming hand and finger surface. While the present grip technology was developed with writing implements in mind, the present grip technology may be readily used with other hand held implements; for example, medical instruments, hand tools, utensils and sporting equipment.

2. Description of the Prior Art

The manner in which an individual grips a writing implement is critical to the comfort of the user as he or she moves the writing implement across a sheet of paper. With this in mind, the designers of writing implements have continually attempted to design writing

implements which enhance the comfort for those individuals using their implements.

Many of the techniques employed in prior art writing implements have made great strides in improving the comfort level associated with the continued use of writing implements. However, a need still exists for writing implements which enhance the comfort of individuals using the writing implements on a continual basis. The present invention provides a writing implement grip improving upon those grips disclosed in the prior art.

5

SUMMARY OF THE INVENTION

It is, therefore, an object of the present invention to provide a grip shaped and dimensioned for use with a writing implement. The grip includes a longitudinally extending tubular shell having an inner surface and an outer surface. The grip also includes a viscoelastic hand/finger surface formed about the outer surface of the tubular shell.

It is also an object of the present invention to provide a grip wherein the tubular shell includes a first end and a second end. The tubular shell further includes an outwardly extending first lip adjacent the first end of the tubular shell and a outwardly extending second lip adjacent the second end of the tubular shell, the first and second lips acting to retain the viscoelastic hand/finger surface in position on the tubular shell.

It is another object of the present invention to provide a grip wherein the first lip extends about the circumference of the tubular shell adjacent the first end of the tubular shell and the second lip extends about the circumference of the tubular shell adjacent the second end of the tubular shell.

It is a further object of the present invention to provide a grip wherein the viscoelastic hand/finger surface is a viscoelastic solid-phase polymer material.

It is also an object of the present invention to provide a grip wherein the viscoelastic solid-phase polymer material is a thermoplastic elastomer.

It is still another object of the present invention to provide a grip wherein the viscoelastic hand/finger surface is a viscous liquid material contained within an elastomeric

bag.

It is yet a further object of the present invention to provide a grip wherein the viscoelastic liquid material is a silicone gel or silicone oil.

It is also an object of the present invention to provide a grip wherein the grip is adapted for selective attachment to the writing implement.

It is another object of the present invention to provide a grip wherein the grip is integrally formed with the writing implement.

It is also an object of the present invention to provide a writing implement including a grip as described above.

Other objects and advantages of the present invention will become apparent from the following detailed description when viewed in conjunction with the accompanying drawings, which set forth certain embodiments of the invention.

20

5

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a side view of a writing implement with the present grip mounted thereon.

Figure 2 is a cross-sectional view of a grip according to a preferred embodiment of the present invention.

Figure 3 is a cross-sectional view of a grip according to a further preferred embodiment of the present invention.

Figure 4 is a cross section of a writing implement with the present grip representing yet another embodiment of the present invention.

Figure 5 is a cross-sectional view of a grip according to a further preferred embodiment of the present invention.

Figure 6 is a cross-sectional view of the present golf grip.

Figure 7 is a perspective view of the present golf grip.

Figure 8 is a cross-sectional view of an alternate embodiment in accordance with the present invention.

Figure 9 is a perspective view of a further embodiment in accordance with the present invention.

Figure 10 is a top view of still another embodiment in accordance with the present invention.

Figure 11 is a perspective view of the embodiment disclosed in Figure 6 secured to a golf shaft.

5

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The detailed embodiments of the present invention are disclosed herein. It should be understood, however, that the disclosed embodiments are merely exemplary of the invention, which may be embodied in various forms. Therefore, the details disclosed herein are not to be interpreted as limited, but merely as the basis for the claims and as a basis for teaching one skilled in the art how to make and/or use the invention.

With reference to Figures 1 through 5, a writing implement grip is disclosed. The grip is designed with a responsive and relatively viscoelastic hand/finger surface. The viscoelastic hand/finger surface provides individuals with a soft and individually conforming gripping surface. For example, and in accordance with a preferred embodiment of the present invention, the conformable, viscoelastic hand/finger surface is a responsive, solid-phase polymer material (Figures 1 and 2) or a gelatinous material interposed within a more resilient material to contain the gelatinous material (Figure 3).

The hand/finger surface of the present grip is an ultra-soft material. This endows the grip with an inherent tactile feel. The grip, as described herein, provides a tacky surface, essential and beneficial for gripping. As those skilled in the art will readily appreciate, the tack level may be readily adjusted with chemical and/or mechanical processing modification. The ultra-soft hand/finger surface can be measured in terms of hardness by the Shore A Durometer Test. The present grips have durometers in this scale between approximately 2 and 35, and more preferably 25 or less.

5

In accordance with a preferred embodiment of the present grip, and with reference to Figures 1 and 2, the grip 10 includes a shell 12 shaped and dimensioned to fit about the grip portion 14 of a convention writing implement 16. As such, the shell 12 includes an inner surface 18 shaped and dimensioned to fit about the main body 20 of the writing implement 16 at a position in line with the grip portion 14 thereof.

It is contemplated that the lower half, or grip portion 14, of the writing implement 16 may be formed with a recess or ridges shaped and dimensioned to engage the grip 10 as it is slipped onto the writing implement 16. In this way, the attached grip 10 will be substantially flush with the overall shape and dimensions of the main body 20 of the writing implement 16.

The outer surface 22 of the shell 12 is shaped and dimensioned to receive the viscoelastic hand/finger surface 24. The shell 12 includes a central section 26 about which the viscoelastic hand/finger surface 24 is positioned. The proximal end 28 and distal end 30 of the shell 12 are respectively provided with lips 32a, 32b circumferentially extending about the shell 12. The lips 32a, 32b are shaped and dimensioned to retain the viscoelastic hand/finger surface 24 about the central section 26 of the shell 12.

The shell 12 may maintain a constant diameter as it extends from the proximal end 28 to the distal end 30. The shape is determined based upon the writing implement for which the grip 10 is designed and may be readily varied without departing from the spirit of the present invention for adaptation to various writing implements. This allows the shell 12 to conform to the shape of conventional writing implements.

5

The shell 12 may be constructed from a variety of elastomers, such as, thermoplastics or thermosets including rubber or synthetic rubber-like materials. In accordance with a preferred embodiment of the present invention, the shell preferably has a Shore A hardness of 20-55. This firmness is necessary to maintain the shape of the grip. It also prevents damage from chemicals and oils, including those produced by human hands. However, other materials may be employed without departing from the spirit of the present invention.

In accordance with the embodiment disclosed in Figures 1 and 2, the viscoelastic hand/finger surface 24 is preferably a viscoelastic solid-phase polymer material. The viscoelastic solid-phase polymer material is preferably a styrenic thermoplastic elastomer containing, for example, KRATON, which is manufactured by Shell Chemical Company.

The viscoelastic hand/finger surface 24 is positioned about the shell 12, and between the proximal and distal lips 32a, 32b. The viscoelastic hand/finger surface 24 is preferably adhered to the central section 26 of the shell 12 by over-molding, co-molding or two-part molding. With related materials over-molding will create a chemical bond, in essence forging one piece containing assimilated parts. This produces a dual durometer grip. This grip would have the advantage of being soft and conformable while being durable and cost effective. It is also contemplated that the viscoelastic hand/finger surface 24 may be adhered to the central section 26 of the shell 12 with an adhesive. As those of ordinary skill in the art will certainly appreciate, other methods for securing the hand/finger surface 24 to the shell 12 may be employed without departing from the spirit of present invention. Where the viscoelastic

5

hand/finger surface 24 is formed from a responsive, and relatively viscoelastic solid-phase polymer material, the outer surface 22 of the viscoelastic hand/finger surface 24 is formed from the same viscoelastic material as the remainder of the hand/finger surface.

An alternate embodiment of the present invention is disclosed in Figure 3. The alternate embodiment is substantially similar to the embodiment described above with reference to Figures 1 and 2, but replaces the viscoelastic solid-phase polymer construction with a viscous liquid material contained in an elastomeric bag.

Specifically, the grip 110 includes a shell 112 shaped and dimensioned to fit about the grip portion 14 of a writing implement 16. As with the prior embodiment, the shell 112 includes a central section 126 about which the soft viscoelastic hand/finger surface 124 is positioned. The proximal and distal ends 128, 130 of the shell 112 are respectively provided with lips 130a, 130b. The lips 130a, 130b are shaped and dimensioned to retain the soft polymer material forming the hand/finger surface 124 about the central section 126 of the shell 112.

In accordance with the embodiment disclosed in Figure 3, the viscoelastic hand/finger surface 124 is a viscous liquid material 134 contained in an elastomeric bag 136. The viscous liquid 134 is preferably a silicone gel or oil and the elastomeric bag is preferably a silicone sheet or a thermoplastic elastomer. While preferred materials are disclosed above, other materials exhibiting similar properties may be used without departing from the spirit of the present invention.

20

5

The viscoelastic hand/finger surface 124 is preferably adhered to the central section 126 of the shell 112 with an adhesive. The attachment could also be accomplished by compressing both ends of the elastomeric bag 136 at the proximal and distal lips 130a, 130b with a chamber and gasket system. As those of ordinary skill in the art will certainly appreciate, other methods for securing the viscoelastic hand/finger surface to the shell may be employed without departing from the spirit of present invention.

The grips 10, 110 described above are designed for selective attachment to an existing writing implement in a manner allowing an individual to readily remove and replace the grips, if necessary. However, and as those skilled in the art will readily appreciate, the underlying concepts of the present grip may be applied in manufacturing an integrally formed writing implement/grip 200. Specifically, and with reference to Figure 4, the shell 212 of the grip 210 is integrally formed as part of the grip portion 214 of the writing implement 216 and the viscoelastic hand/finger surface 224 is coupled directly thereto. Other manufacturing techniques in accordance with the spirit of the present invention are certainly possible and considered to be well within the scope of the present invention.

In accordance with the preferred embodiments of the present invention, the soft polymer material forming the hand/finger surface is approximately 0.02 to 0.50 inches thick and the elastomeric shell is preferably less than 0.5 inches thick. In this way, the present grip substantially conforms to ergonomically desirable writing implement dimensions.

With reference to Figure 5, an alternate embodiment for a responsive grip is also

5

contemplated. Specifically, a one piece grip 310 manufactured exclusively from a viscoelastic solid-phase polymer material is disclosed. The grip 310 includes a longitudinally extending tubular shell 312 having an inner surface 318 shaped and dimensioned for attachment to the grip portion 14 of a writing implement 16 and an outer surface 322 shaped and dimensioned for gripping by an individual. The shell 312 is preferably manufactured from a silicone, thermoset elastomer containing, for example, SILASTIC, manufactured by Corning STI, although other materials may be used without departing from the spirit of the present invention. As with the shell discussed above with reference to Figures 1-4, the tubular shell shown 310 in Figure 5 is shaped and dimensioned for use as a gripping surface on a writing implement 16.

It should be appreciated that the elastomer containing, for example, KRATON or liquid silicones (such as, SILASTIC), may be altered via chemical and manufacturing processes. This alteration would likely include the softening of the thermoplastic elastomer. Also other treatments may be used without departing from the spirit of the present invention. The elastomer may also be modified to enhance its performance characteristics. For example, ultra-violet protection and/or fillers, such as Kevlar (an aramid fiber manufactured by DuPont), may be added to enhance the performance of the elastomer.

The provision of a responsive viscoelastic polymer finger surface in all three embodiments, provides users with soft and individually conforming grips. In this way, the grips are designed to enhance the tactile feel of the instrument. This improves the user's

ability to work. The soft viscoelastic surface also reduces finger and hand fatigue. The structure of the present invention is also easy to manufacture, either through the use of extrusion or injection molding. It is further contemplated that other manufacturing steps may be involved when the viscous liquid grip is utilized.

5

The practicality and durability of the present grips are also noteworthy. The inner shell on the grip provides a rigid and long-lasting shape or housing. The shell's strength is maintained even with extended use. The soft outer surface is protected and partially encased by this shell. Unlike foam and other materials, liquids will not adversely affect the grip. Its improved performance is observed with regard to finger oil absorption. The two part design prevents excessive absorption. This greatly reduces the degradation and swelling of the grip with use. The two part grip holds precise its exacting dimensions. The firm and precisely designed shell also makes installation of the grip easier. It will not catch and wrinkle as it is assembled like a soft one-piece rubber grip would.

The present grips also provide greater shock absorption and vibration dampening.

Clearly, with regard to various sports implements and other handles, this feature is desirable and helpful to the user. The grips described above provide much more shock absorption than other grips on the market.

The ergonomic emphasis of this design is positive. Its use may help lower the rate of finger/hand injuries caused by excessive pressure and rigid surfaces.

As previously mentioned the invention relates generally to conformable grips useful in

5

hand gripped items. With this in mind, an alternate embodiment of the present grip for use in conjunction with a golf grip is disclosed in Figures 6 to 8. The golf grip 210, 310 is designed with a responsive and relatively viscoelastic hand surface 212, 312. The viscoelastic hand surface 212, 312 provides golfers with a soft and individually conforming hand surface. For example, the viscoelastic hand surface 212, 312 may be a responsive and relatively viscoelastic solid-phase polymer material (Figures 6 and 7) or a gelatinous material interposed within a more resilient material to contain the gelatinous material (Figure 8).

The hand surface of the present grip is an ultra-soft material. This also endows the product with an inherent tactile feel. The grip, as described herein, provides a tacky surface, essential and beneficial for gripping. The ultra-soft hand surface can be measured in terms of hardness by the Shore A Durometer Test. The present grips have durometers in this scale between approximately 2 and 40.

In accordance with a preferred embodiment of the present golf grip 210, and with reference to Figures 6 and 7, the golf grip 210 includes a shell 214 shaped and dimensioned to fit about the proximal end 216 of a golf club shaft 218. As such, the shell 214 includes an inner surface 232 shaped and dimensioned to fit about the golf club shaft. The outer surface 234 of the shell 214 is shaped and dimensioned to receive the viscoelastic hand surface 212 in a manner that will be discussed in greater detail below.

As with most golf grips, the present golf grip 210, and the shell 214, are tapered as they extend from the closed proximal end 236 to the open distal end 238. This allows the shell 214

5

to conform to the shape of conventional golf club shafts 218.

The shell 214 may be constructed from a variety of soft elastomers, such as, rubber or synthetic rubber-like materials. However, other materials may be employed without departing from the spirit of the present invention.

The shell 214 includes a central section 220 about which the viscoelastic hand surface 212 is positioned. The proximal end 222 and distal end 224 of the shell 214 are respectively provided with lips 226, 228 circumferentially extending about the shell 214. The lips 226, 228 are shaped and dimensioned to retain the viscoelastic hand surface 212 about the central section 220 of the shell 214.

In accordance with the embodiment disclosed in Figures 6 and 7, the viscoelastic hand surface 212 is preferably a viscoelastic solid-phase polymer material. The viscoelastic solid-phase polymer material is preferably a styrenic thermoplastic elastomer containing, for example, KRATON, which is manufactured by Shell Chemical Company.

The viscoelastic hand surface 212 is positioned about the shell 214, and between the proximal and distal lips 226, 228. The viscoelastic hand surface 212 is preferably adhered to the central section 220 of the shell 214 with an adhesive. It is also contemplated that the hand surface 212 may be adhered to the central section 220 of the shell 214 by over molding. With related materials over molding would create a chemical bond, in essence forging one piece containing assimilated parts. As those of ordinary skill in the art will certainly appreciate, other methods for securing the hand surface 212 to the shell 214 may be employed without

20

departing from the spirit of present invention. Where the viscoelastic hand surface 212 is formed from a responsive, and relatively viscoelastic solid-phase polymer material, the outer surface 230 of the viscoelastic hand surface 212 is formed from the same viscoelastic material as the remainder of the hand surface 212.

5

An alternate embodiment of the present invention is disclosed in Figure 8. The alternate embodiment is substantially similar to the embodiment described above with reference to Figures 6 and 7, but replaces the viscoelastic solid-phase polymer construction with a viscous liquid material contained in an elastomeric bag.

Specifically, the golf grip 310 includes a shell 314 shaped and dimensioned to fit about the proximal end of a golf club shaft. As with the prior embodiment, the shell 314 includes a central section 320 about which the soft viscoelastic hand surface 312 is positioned. The proximal and distal ends 322, 324 of the shell 314 are respectively provided with lips 326, 328. The lips 326, 328 are shaped and dimensioned to retain the soft polymer material forming the hand surface 312 about the central section 320 of the shell 314.

15

In accordance with the embodiment disclosed in Figure 8, the viscoelastic hand surface 312 is a viscous liquid material 336 contained in an elastomeric bag 338. The viscous liquid 336 is preferably a silicone gel or oil and the elastomeric bag 338 is preferably a silicone sheet or a thermoplastic elastomer. While preferred materials are disclosed above, other materials exhibiting similar properties may be used without departing from the spirit of the present invention.

20

The viscoelastic hand surface 312 is preferably adhered to the central section 320 of the shell 314 with an adhesive. The attachment could also be accomplished by compressing both ends of the elastomeric bag 338 at the proximal and distal lips 326, 328 with a chamber and gasket system. As those of ordinary skill in the art will certainly appreciate, other methods for securing the viscoelastic hand surface 312 to the shell 314 may be employed without departing from the spirit of present invention.

The present golf grip 210, 310 is designed such that it may be placed about the proximal end of the golf club shaft in much the same manner that conventional golf grips are placed about the proximal end of a golf club shaft. As such, the present golf grip 210, 310 may be used as a replacement grip for worn grips or grips placed upon a golf club during the manufacture of the golf club.

In accordance with the preferred embodiments of the present invention, the soft polymer material forming the hand surface 212, 312 is approximately 1/16" - 1/4" thick and the elastomeric shell 214, 314 may be less than 1/8" thick, but up to 1/4" thick. In this way, the present grip 210, 310 has substantially the same dimensions as conventional golf grips.

With reference to Figures 9 through 11, alternate embodiments for a responsive grip are also contemplated. Specifically, Figure 9 discloses a one piece grip 410 manufactured exclusively from a viscoelastic solid-phase polymer material. The grip 410 includes a longitudinally extending tubular shell 412 having an inner surface 414 shaped and dimensioned for attachment to a golf club shaft and an outer surface 416 shaped and

dimensioned for gripping by an individual. The shell 412 is preferably manufactured from a styrenic thermoplastic elastomer containing, for example, KRATON, manufactured by Shell Chemical Company, although other materials may be used without departing from the spirit of the present invention.

As with the shell discussed above with reference to Figures 6 to 8, the tubular shell 412 shown in Figure 9 is shaped and dimensioned for use as a golf club grip. With this in mind, the grip is slightly tapered from its closed first end 418 to its open second end 420.

The embodiment disclosed in Figures 10 and 11 is a wrap 510 for application to grips. The wrap is a longitudinally extending strip 512 of a viscoelastic solid-phase polymer material having a first end 514 and a second end 516, wherein the first end 514 is cut at an oblique angle to facilitate attachment of the strip 512 to the handle 518 of a sports, or other, implement. The strip 512 is of a length sufficient to be wrapped about the handle 518 and to act as a grip for the implement. The wrap 510 is preferably manufactured from a thermoplastic elastomer, for example, KRATON, manufactured by Shell Chemical, although other materials may be used without departing from the spirit of the present invention. The wrap is, again, composed of the ultra-soft material, which provides unprecedented benefits and advantages to the user.

As shown in Figure -, the wrap 510 is secured to the handle 518 of a sports implement, or other implement, by simply encircling the handle in a conventional manner. Additionally, all-purpose adhesive tape or glue may be placed between the handle 518 and the wrap 510 to ensure the secure attachment of the wrap 510 to the handle 518.

It should be appreciated that the styrenic thermoplastic elastomer containing, for example, KRATON, may be altered via chemical and manufacturing processes. This alteration would likely include the softening of the thermoplastic elastomer. Also other treatments may be used without departing from the spirit of the present invention.

5

The provision of a responsive viscoelastic polymer hand surface provides golfers with a soft and individually conforming hand surface. In this way, the present grips are designed to enhance the feel of the golf club, and, thereby, improve the golfer's ability to strike a golf ball. A soft grip surface prompts the golfer to use a softer touch in putting and it helps to avoid excessive squeezing on other clubs. The soft viscoelastic hand surface also reduces hand fatigue associated with gripping a hard hand surface. In addition, the use of an elastomeric shell with a responsive viscoelastic polymer material encased therein makes the present golf grip easy to manufacture and place upon the proximal end of a golf club shaft for use by a golfer.

15

The present grips also provide greater shock absorption and vibration dampening. Clearly, with regard to various sports implements and other handles, this feature is desirable and helpful to the user. The grips described above provide much more shock absorption than other grips on the market.

While the preferred embodiments have been shown and described, it will be understood that there is no intent to limit the invention by such disclosure, but rather, is intended to cover all modifications and alternate constructions falling within the spirit and

20

scope of the invention.

CLAIMS

- 1. A writing implement, comprising:
 - a main body having a gripping portion upon which a grip is mounted;
- the grip including a longitudinally extending tubular shell having an inner surface
- 5 abutting with the main body and an outer surface, and a viscoelastic hand/finger surface
 - formed about the outer surface of the tubular shell.
 - 2. A writing implement according to claim 1, wherein the grip readily removable from the main body of the writing implement.
 - 3. A writing implement according to claim 2, wherein the viscoelastic hand/finger surface is a viscoelastic solid-phase polymer material.
 - 4. A writing implement according to claim 3, wherein the viscoelastic solid-phase polymer material is a thermoplastic elastomer.
 - 5. A writing implement according to claim 2, wherein the viscoelastic hand/finger surface is a viscous liquid material contained within an elastomeric bag.

- 6. A writing implement according to claim 5, wherein the viscoelastic liquid material is a silicone gel or silicone oil.
- 7. A writing implement according to claim 1, wherein the grip is integrally formed with the main body of the writing implement.
 - 8. A writing implement according to claim 7, wherein the viscoelastic hand/finger surface is a viscoelastic solid-phase polymer material.
 - 9. A writing implement according to claim 8, wherein the viscoelastic solid-phase polymer material is a thermoplastic elastomer.
 - 10. A writing implement according to claim 7, wherein the viscoelastic hand/finger surface is a viscous liquid material contained within an elastomeric bag.
 - 11. A writing implement according to claim 10, wherein the viscoelastic liquid material is a silicone gel or silicone oil.

12. A grip adapted for attachment to an implement including a handle, comprising: a longitudinally extending tubular shell including an inner surface shaped and dimensioned for attachment to the handle of the implement and an outer surface; and


a viscoelastic hand surface having a thickness secured about the outer surface of the tubular shell, wherein the tubular shell includes a first end and a second end, and the tubular shell includes an outwardly extending first lip adjacent the first end of the tubular shell and a outwardly extending second lip adjacent the second end of the tubular shell, the first and second lips defining a central section within which the viscoelastic hand surface is positioned, wherein the central section has a depth as defined by the first and second lips which is substantially the same as the thickness of the viscoelastic hand surface such that the first and second lips acting to retain the viscoelastic hand surface in position on the tubular shell.


- 13. A grip according to claim 12, wherein the first lip extends about the circumference of the tubular shell adjacent the first end of the tubular shell and the second lip extends about the circumference of the tubular shell adjacent the second end of the tubular shell.
- 14. A grip according to claim 12, wherein the viscoelastic hand surface is a viscoelastic solid-phase polymer material.


- 15. A grip according to claim 14, wherein the viscoelastic solid-phase polymer material is a thermoplastic elastomer.
- 16. A grip according to claim 12, wherein the viscoelastic hand surface is a viscous liquid material contained within an elastomeric bag.
 - 17. A grip according to claim 16, wherein the viscoelastic liquid material is a silicone gel or silicone oil.
 - 18. A grip according to claim 12, wherein the tubular shell is a soft elastomer.
 - 19. A grip according to claim 12, wherein the grip is shaped and dimensioned for use as a golf club grip.
- 15 20. A grip according to claim 19, wherein the tubular shell is substantially cylindrical shaped with a slight taper.


ABSTRACT OF THE DISCLOSURE


A grip adapted for attachment to a writing implement is disclosed. The grip includes a longitudinally extending tubular shell having an inner surface and an outer surface. The grip further includes a viscoelastic hand/finger surface formed about the outer surface of the tubular shell.


















FIG. 7









IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

DECLARATION FOR PATENT APPLICATION

INVENTOR(S): Benjamin J. Kwitek

TITLE : VISCOELASTIC GRIP FOR A WRITING

INSTRUMENT

DOCKET NO. : KWI-003

TO THE HONORABLE COMMISSIONER OF PATENTS AND TRADEMARKS:

As a below named inventor, I hereby declare that:

This declaration is of the following type: (check one applicable item below)

<u>X</u>	original
	design
	supplemental

NOTE: If the declaration is for an International Application being filed as a divisional, continuation or continuation-in-part application do <u>not</u> check next item; check appropriate one of last three items.

___ national stage of PCT

NOTE: If one of the following 3 items apply then complete and also attach ADDED PAGES FOR DIVISIONAL, CONTINUATION OR CIP.

divisional
continuation
x continuation-in-part (CIP)

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor

(if plural names are listed below) of the subject matter which is
claimed and for which a patent is sought on the invention entitled
VISCOELASTIC GRIP FOR A WRITING INSTRUMENT, the specification of
which is attached hereto unless the following is checked:
was filed on as United States Application Number or
PCT International Application Number, and was amended on
(if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(d) or 265(b) of any foreign application(s) for patent or inventor's certificate or 365(a) of any PCT international application which designates at least one country other than the United States of America, listed below and have also identified below any foreign application for patents or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Applications:

Priority Claimed:

(Day/Month/Year Filed)

Yes

No

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

60/163, 259 11/03/99 Pending
(Application No.) (Filing Date) (Status - patented, pending, abandoned)

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the National or PCT international filing date of this application.

09/173,445	10/16/98	Pending
(Application No.)	(Filing Date)	(Status - patented, pending, abandoned)
60/062,215	10/16/97	Abandoned
(Application No.)	(Filing Date)	(Status - patented, pending,
(11pp110001011 1.01)	(5	abandoned)

that the part of the the transition of the trans

As the inventor, I hereby appoint the following attorney(s) and/or agent(s) of AQUILINO, WELSH & FLAXMAN, P.C. to prosecute this application and transact all business in the U.S. Patent and Trademark Office connected therewith. Name and registration number are listed below.

NICHOLAS J. AQUILINO 24,527

JOHN L. WELSH 33,621

HOWARD N. FLAXMAN 34,595

Please send correspondence to:

Direct telephone calls to:

Howard N. Flaxman

Howard N. Flaxman

AQUILINO, WELSH & FLAXMAN, P.C.

(703) 920-1122

2341 Jefferson Davis Hwy

Suite 112

Arlington, Virginia 22202

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full	name	οf	sole	or	first	inventor:
------	------	----	------	----	-------	-----------

Benjamin J. Kwitek

Residence : Canon City, CO

Citizenship: United States of America

Post Office Address: 1061 Valley View Drive

Canon City, CO 81212

Date: 11/03/00 Signature: Equation Timble